

HOLDFAST

Right First Time!

Innovation
Plus
Imagination

Need the job done quickly..?



Gorilla **Grip**

INSTANT

LASTS
50+
YEARS



**Construction
Adhesive**
10min.

- ✓ Will Stick to damp surfaces
- ✓ 100% solids. No Shrinkage
- ✓ Tested to stick to LSOP timber
- ✓ Wood, metal, wood, stone, concrete, plastic



FOR HELP PHONE 07 847 5540

**INSTANT****Product Code:** 19288 (310ml)**Product Name:** HOLDFAST® Gorilla Grip Instant
- 10 minute**Description**

HOLDFAST® Gorilla Grip Instant – 10 Minute Cure is a translucent polyurethane adhesive with a pasty (thixotropic) structure which makes the adhesive suitable for vertical application. The adhesive cures through reaction with moisture from the substrate and forms a strong, durable, water resistant connection. As the adhesive can slightly foam during curing, this gives the adhesive gap filling properties.

Technical Data

Basis:	Polyurethane
Application Temperature:	+5/+30
Density:	1,1 g/ml
Solids:	99 %
Open time:	5 min
Hand tight after:	20 min
Final adhesion after:	24 hours
Coverage:	200-300 g/m ²
Frost resistant till -15°C during transport:	Yes
Shelf life between +5°C and +25°C:	12 months
Temperature resistance after curing:	-30/+100°C
Water resistance after curing:	B4

Applications

- As a wood adhesive
- To bond metal, wood, stone, concrete, plastic and isolating materials like PU foam, PS foam, Rock wool and glass wool.
- Gluing sandwich constructions.

Appearance

Colour: Translucent

Packaging: 310ml

Surfaces

Preparation: Surfaces have to be dry, clean and sounds.

Application

Method: Apply the adhesive from the cartridge onto one side. For efficient curing it is necessary that one of the surfaces is porous. Put the materials to be bonded together within the open time. Prevent any displacement. Keep the connection under pressure for approximately 20-30 minutes. Adhesion tests prior to the application are recommended.

Application Limitations

Among others not recommended for locations subject to continuous water emersion.

Foam formation of the adhesive as a result of insufficient pressure or an insufficient fit leads to a decreased end strength. Do not use below +5°

Health and Safety Recommendation

- Apply the usual industrial hygiene
- Please refer to the MSDS for more detailed information.

Remark

The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.

Last Updated: 10th May 2006**THE BEST FOR DURABILITY****THE BEST FOR STRENGTH****THE BEST WALLBOARD ADHESIVE****DIRECT STICK WALLBOARD CONSTRUCTION ADHESIVE**

- ✓ Will Stick to damp surfaces
- ✓ 100% solids. No Shrinkage
- ✓ Tested to stick to LOSP timber
- ✓ Sticks to more substrates than any other

**YOU HAVE A CHOICE..****original****EXPRESS****INSTANT****.. NOW YOU DECIDE**

9 551414 192887

Code: FLYER11
Gorilla Grip Instant Flyer

HOLDFAST NZ LTD
14 Avalon Drive, SH 1, Nawton 3200
PO Box 4206, Hamilton East 3247
Hamilton, New Zealand
Ph: (07) 847 5540, Fax (07) 847 0324,
Email: sales@holdfast.co.nz
http://www.holdfast.co.nz