

CHECK OUT Their New Look...



- ✓ Ideal for expansion joints
- ✓ BRANZ Appraised No.419
- ✓ Superior flexibility
- ✓ Excellent UV resistance

White cartridge #20067
Grey cartridge #20068
Black cartridge #20070

White sausage #20073
Grey sausage #20072
Black sausage #20071



- ✓ Superior versatility
- ✓ High initial tack
- ✓ Sticks to all substrates
- ✓ Excellent UV resistance

White cartridge #20303
Grey cartridge #20302
Black cartridge #20301
Bronze cartridge #20304

FixAll HG is a high performance MS adhesive with powerful bond strength and high initial tack. Will adhere almost anything!

Features	Superior versatility, high initial tack, withstands mould growth, UV resistant, no solvents or isocyanates, *paintable with waterbased paints, low VOC content (34 gram/litre), waterproof.
Uses & Substrates	<i>Limited by your imagination!</i> Concrete, marble, granite, timber, limestone, cork, polystyrene, mirrors, tiles, brick, stone etc.
Temperature	Bond will be maintained between -40°C and 90°C when cured.
Cure Time	2-3mm / 24hour (20°C/65% R.V)
Movement	Up to 20%
Clean Up	Before cure – Bulldog Cleaner

Directions: (Warning: Product has limitations. Please ensure when using this product that you read the instructions carefully. Test is Best. Refer to datasheet on website. www.holdfast.co.nz) Ensure surface is clean, free of dust, grease and is not wet**. Porous substrates may be primed with Holdfast Primer 150. Non porous substrates may be primed with Holdfast 696 Surface Activator. Cut tip off cartridge, load into Gorilla Pro Gun +Plus or Fix All Ultimate Gun, and cut nozzle to desired size. Dispense a bead of adhesive onto one surface, and press the surfaces firmly together.

First Aid: If in doubt or with persisting symptoms, obtain medical attention. Never put anything through the mouth of an unconscious person. Swallowed: Do NOT induce vomiting. Wash out mouth with water and obtain medical attention. Eye contact: Irrigate with eyewash solution or clean water, holding the eyelids part for at least 10 minutes. Obtain medical attention. Skin Absorption: Remove contaminated clothing. Wash skin with soap and water. Do NOT use solvents or thinners. Inhalation: Remove the victim into fresh air. Seek medical advice.

Safe Handling Information: Observe normal hygiene standards. Do not discharge the waste into the drain. Keep containers dry and closed. Keep away from foodstuffs. Wash hands thoroughly before breaks and at the end of the working day. Store in a cool and well ventilated place in the original containers.

**Fix All HG will stick to damp surfaces. A surface is considered wet when moisture transfer occurs from the substrate.

FixAll 220 is a high performance MS sealant, with superior flexibility, which makes it ideal for expansion joints or joints subject to (high) movement.

Features	UV resistant, low VOC content (<32 gram/litre), waterproof, *paintable with waterbased paints, withstands mould growth, no bubble formation, no solvent or isocyanates, E2/AS1 compliant, Agriquality Approval (REF #h1540), BRANZ Appraisal No.419, Conforms to ISO 11600-F-25LM.
Uses & Substrates	<i>Limited by your imagination!</i> Expansion and connection joints, sealing prefabricated buildings, movement joints, sealing windows & doors.
Temperature	Bond will be maintained between -40°C and 90°C when cured.
Cure Time	2mm / 24hour (20°C/65% R.V)
Movement	+ / - 25%
Clean Up	Before cure – Bulldog Cleaner

Directions: (Warning: Product has limitations. Please ensure when using this product that you read the instructions carefully. Test is Best. Refer to datasheet on website. www.holdfast.co.nz) Ensure surface is clean, free of dust, grease and is not wet**. For porous surfaces, where water pressure may occur Holdfast Primer 150 may be applied. Non porous substrates may be primed with Holdfast 696 Surface Activator. Cut tip off cartridge, load into Gorilla Pro Gun +Plus or Fix All Ultimate Gun, and cut nozzle to desired size. Dispense a bead of adhesive onto one surface, and press the surfaces firmly together. Tool with soapy solution before skin formation.

Joint Dimensions: Width = Minimum: 5mm, Maximum: 30mm, Recommended Depth = 1/2 width, and use the appropriate size of Holdfast Gator PEF Rod.

First Aid: In in doubt or with persisting symptoms, obtain medical attention. Never put anything through the mouth of an unconscious person. Swallowed: Never give water to an unconscious person. Do not induce vomiting. Seek medical advice. Eye contact: Rinse immediately with plenty of water. Seek medical advice. Skin Absorption: Rinse immediately with plenty of water. If irritation persists seek medical advice. Inhalation: Remove the victim into fresh air. Seek medical advice.

Safe Handling Information: Observe normal hygiene standards. Keep containers dry and closed. Keep away from foodstuffs. Store at room temperature in a well ventilated place in the original containers. In case of insufficient ventilation keep naked flames/sparks away.

**Fix All 220 will stick to damp surfaces. A surface is considered wet when moisture transfer occurs from the substrate.



- ✓ Ideal for expansion joints
- ✓ BRANZ Appraised No.419
- ✓ Superior flexibility
- ✓ Excellent UV resistance

White cartridge #20067
Grey cartridge #20068
Black cartridge #20070
White sausage #20073
Grey sausage #20072
Black sausage #20071



- ✓ Superior versatility
- ✓ High initial tack
- ✓ Sticks to all substrates
- ✓ Excellent UV resistance

White cartridge #20303
Grey cartridge #20302
Black cartridge #20301
Bronze cartridge #20304

