



Backing Rod

Complies with ASTM standard as per NZ Building Code

NOW IN REELS!

AVAILABLE SIZES

- 39172 6mm x 50m REEL A
- 39147 6mm x 250m
- 39141 8mm x 25m
- 39171 8mm x 50m REEL A
- 39148 8mm x 300m
- 39142 10mm x 25m
- 39170 10mm x 50m REEL A
- 39149 10mm x 600m
- 39143 13mm x 25m
- 39169 13mm x 50m REEL B
- 39150 13mm x 400m
- 39144 15mm x 25m
- 39164 15mm x 50m REEL B
- 39151 15mm x 250m
- 39145 20mm x 25m
- 39168 20mm x 50m REEL B
- 39152 20mm x 150m
- 39146 25mm x 25m
- 39167 25mm x 50m
- 39153 25mm x 100m
- 39166 30mm x 50m
- 39154 30mm x 80m
- 39160 40mm x 2m
- 39161 50mm x 2m

Gator® PEF Rod is designed to control the depth of the sealant or expanding foam, such as Gorilla® Nailpower®, around the window, door or other penetration openings to ensure it does not completely fill the cavity.

Gator® PEF Rod also ensures the correct sealant depth when filling expansion joints, while at the same time ensuring the sealant does not adhere to the rod so it can move freely.

Holdfast® has now released the most common sizes in more practical, user friendly reels. The attractive new packaging allows the user to easily dispense. Finding the end of the reel is now simple, as it is identified with a bright blue sticker.

The distinctive yellow box on the front of the reel, clearly states the width and length of the rod, which makes it easy to find the correct size on the shelf. Each reel gives clear instructions of use, which includes diagrams and an explanation on how to build a code compliant air seal.

The back of the reel assists with finding the right size for the job by having a chart of 'actual size' drawing of each size rod available.

Gator® PEF Rod is available in a wide range of sizes. To make it easy for shelf display there are two size reels (A and B) which can be attractively stacked. Those available in the new reel packaging are marked in chart.

You know you can trust Gator® to roll out the best!

