

Shakes & Shingles

Cedar Hip & Ridge

Grades: PREMIUM GRADE: clear heartwood. 100% edge grain
 NUMBER 1 GRADE: clear heartwood, maximum 20% flat grain. Not available in Shingle Hip & Ridge.
 NUMBER 2 GRADE: lower half is clear, flat and cross grains allowed, tight knots and defect allowed in the upper half only. Not available in Handsplit-Resawn Hip & Ridge.
CCA and Fire retardant treatments available on request.

Lengths: Tapersawn or Handsplit-Resawn: 24-inch (610mm), 18-inch (455mm).
 Shingle: 18-inch (455mm), 16-inch (405mm).

Thicknesses: Tapersawn : 5/8-inch (16mm), 3/4-inch (19mm) Heavy.
 Shingle: 5pcs/2-inch (5/50mm), 5pcs/2¼-inch (5/55mm).
 Handsplit-Resawn: 1/2-inch (13mm), ¾-inch (19mm).
Other thicknesses available on application.

Widths: Tapersawn or Handsplit-Resawn: For 24-inch length, 9" Wide. For 18-inch length, 8½" Wide. Extra Wide also available 11¼-inch.
 Shingle: 16-inch & 18-inch ridge both 7-inches wide.

Roof Pitch: 4:12 (19°) minimum, (lower slopes require special application).

Maximum Recommended Exposure:

TAPERSAWN / HANDSPLIT-RESAWN HIP & RIDGE			
24-INCH (610mm)		18-INCH (455mm)	
PREM & No.1	No.2	PREM & No.1	No.2
10" (250mm)	7 ½" (190mm)	7 ½" (190mm)	5 ½" (140mm)

SHINGLE HIP & RIDGE			
18-INCH (455mm)		16-INCH (405mm)	
PREM	No.2	PREM	No.2
5 ½" (140mm)	4 ½" (115mm)	5" (127mm)	4" (100mm)

