

Shakes & Shingles

Cedar Shingles

Types: **FIVE X** - 16-inch (405mm)
PERFECTIONS - 18-inch (455mm)
ROYALS - 24-inch (610mm)

Grades: **NUMBER 1 GRADE:** clear heartwood. 100% edge grain, no defects
NUMBER 2 GRADE: clear face from butt-end: 10-inch for FiveX, 11-inch for Perfections, 16-inch for Royals. Limited sapwood, flat grain, knots & defects above clear portion.
NUMBER 3 GRADE: clear face from butt-end: 6-inch for FiveX and Perfections, 16-inch for Royals. Limited sapwood, flat grain, knots & defects above clear portion.

CCA and Fire retardant treatments available on request.

Thicknesses: 5pcs /2" (5/50mm) FIVE X
 5pcs /2 ¼" (5/55mm) PERFECTIONS
 4pcs /2" (4/50mm) ROYALS

Widths: Random, 4-inch (100mm) minimum. 10% 3-inch (75mm) permitted for No.1 Grade FIVE X & PERFECTIONS only, 20% permitted for No.2 Grade, 30% permitted for No.3 Grade. No maximum.

Roof Pitch: 4:12 (19°) minimum, (lower slopes require special application).

Maximum Recommended Exposure:

	FIVE X			PERFECTIONS			ROYALS		
	16-INCH (405mm)			18-INCH (455mm)			24-INCH (610mm)		
	No.1	No.2	No.3	No.1	No.2	No.3	No.1	No.2	No.3
ROOF	5" (127mm)	4" (100mm)	3 ½" (90mm)	5 ½" (140mm)	4 ½" (115mm)	4" (100mm)	7 ½" (190mm)	6 ½" (165mm)	5 ½" (140mm)
WALL	7 ½" (190mm)	7 ½" (190mm)	6" (150mm)	8 ½" (215mm)	8 ½" (215mm)	6" (150mm)	11 ½" (290mm)	11 ½" (290mm)	10" (250mm)