



Fix Admix

SBR Latex Admixture specially formulated for further enhancing bond strength, flexibility and durability of tiling adhesive.

PRODUCT

FIX ADMIX is a high performance liquid latex admixture formulated to mix with tile setting products in replacement of water to meet the higher requirement of interior and exterior tiling works onto concrete, brickwork, masonry and existing tiled surface including gypsum wallboards. Ideal for wall and floor installation of marble, slate, granite, ceramic and homogenous tiles.

TECHNICAL DATA AND PHYSICAL PROPERTIES

Base Material	Modified SBR Latex
Colour	Milky White (Wet). Clear (Dry)
Compressive Strength	Exceeds 20N/mm ²
Shear Bond Strength	3.4N/mm ² (35 kg/cm ²)
Tensile Strength (ASTM C190)	4.6N/mm ² (47 kg/cm ²)

RECOMMENDED MIX

Premixed Plasters	Fix Admix	Dosage/25 kg
E.MIX Tile Fix	Dilution to be recommended according to type of receiving substrate	Approx 8.0 ltr
E.MIX Basic Fix		Approx 7.0 ltr
E.MIX Easi Fix		Approx 5.0 ltr
E.MIX Marble Fix		Approx 4.5 ltr

Note: Refer to SUPER FIX/TILE FIX/BASIC FIX/EASI FIX/MARBLE FIX Technical Data Sheets for application procedure.

PROCEDURE

The substrate should be sound and free from materials affecting adhesion. Mix BASIC FIX into the correct amount of water or FIX ADMIX. Allow mixture to stand for 10 minutes and mix again. Application with notched trowel onto substrate or applying onto backface of tile are both recommendable. For big tiles and tile with high ridges, combination of both methods gives best result. Substrates on which mortar has been spread should be tiled within 5 minutes. The tiles should be firmly pressed onto the sub-base and immediately knocked into position. Tiling should not be done under extremely hot, windy and rainy conditions to avoid adverse effects on bond strength. Soaking of tiles in water prior to tiling is not recommended.

PACKING AND STORAGE

BASIC FIX is available in 20 ltr cans or 150 ltr drums. Store in a cool dry place away from extreme temperature. Stir before use.

Note: No further dilution of FIX ADMIX is permitted at site. Refer to tile setting products Technical Data Sheet for application procedures. Do not apply directly to plywood, chipboard, particleboard, decorative laminates or resilient flooring. Because it is not possible to give specific instructions for the various site conditions or to control the applications, the information on this technical data sheet is for general guidance only.