



Marble Fix

Cement-based thick-bed marble fixing mortar for floor and wall.

PRODUCT

MARBLE FIX is a high quality water resistant dry-set mortar specially designed for fixing marble onto floor and wall between 5 - 12mm thick. Application is by means of buttering onto backside of marble slab to ensure full coverage. Notched trowel with higher ridges can also be used for applying MARBLE FIX.

MARBLE FIX is also suitable for installing granite tiles. To enhance product performance in harsher conditions or to meet higher requirements; E-MIX FIX ADMIX is recommended to be added to MARBLE FIX in replacement of water. Suitable substrates are concrete and cement, sand/plaster.

TECHNICAL DATA AND PHYSICAL PROPERTIES

Colour	Beige
Binder	White Cement
Filler	Graded sand
Additives	Water soluble additives to improve workability, open time, bond strength etc
Pot life	1 hour
Consumption	Approx 1.5 kg/m ² /mm thick
Water Demand	Approx 18% or 4.5l per 25 kg bag

Exceed requirement of ANSI A118.1 1992 and A118.4 1992 (when mixed with E MIX FIX ADMIX)

Technical References are available upon request

PROCEDURE

The substrate should be sound and free from materials effecting adhesion. Mix MARBLE FIX into the correct amount of water or E-MIX FIX ADMIX, Allow mixture to stand for 10 minutes and mix again. Apply the mortar onto backside of tiles. Pressed tiles onto substrate firmly and knock tiles into position.

PACKING AND STORAGE

MARBLEFIX is delivered in 25 kg bags. Storage life is 6 months if product is stored in a dry place.

Note: Because it is not possible to give specific instructions for the various site conditions or to control the applications, the information on this technical data sheet is for general guidance only.