



how to

Fix Drywall to Drywall Create the Perfect Finish with No Nail Holes!




STEP 1

Ensure the drywall is clean & free from oil or dirt.




STEP 2

Using a 10mm x 10mm sized bead apply Gorilla Grip® using a Gorilla® Pro Gun.



STEP 3

Apply strips of Gator® Double Sided Tape* between each bead of Gorilla Grip®



STEP 4

Gently press the drywall against the adhesive to join. Allow 1 hour to cure.

*Soon to be available in double-sided adhesive dots for ease of use.

... why Gorilla® Grip®?

Gorilla® Grip® eliminates all risks, with its high bond strength and fast cure. Guaranteed to stick drywall to drywall with the perfect finish!



- ✓ Guaranteed to avoid nail holes = Perfect finish!
- ✓ Guaranteed to not shrink = Use less!
- ✓ Guaranteed to cure in 1 hour = Instant walls!
- ✓ NO RISKS, TRUST Gorilla Grip, Guaranteed to work!

... what you need



OR



+



+



GUARANTEED NO RISK!

*NOTE: This information is intended as a guide only. If you are unsure please contact us for more detail. No responsibility will be accepted for incorrect installation. Test is best. Please refer to technical datasheet on our website. www.holdfast.co.nz

Brett Henderson
Brett Henderson
Managing Director, Holdfast NZ Ltd