



how to

Fix Seratone Panels Guarantees a safe secure bond!




STEP 1

Clean non porous surface by wiping with Holdfast® 696 Surface Activator.




STEP 2

Apply Gator® Bond Tape to frame.



STEP 3

Apply continuous bead of Fix All® 220 Sealant using a Gorilla® Pro Gun.



STEP 4

Gently press the Seratone panel against adhesive to join.* Allow 24 hours for full cure.

*Roll or press firmly over all areas of framing to ensure consistent contact between Seratone panel and the Gator® Bond and Nailpower® Solvent Free

... why Fix All® 220 Sealant?

Fix All® 220 Sealant is a high performance MS sealant, with superior flexibility. Guaranteed to stick!



- ✓ Guaranteed low VOC content = Environmentally friendly!
- ✓ Guaranteed for use on expansion joints
- ✓ Guaranteed for interior and exterior use
- ✓ NO RISKS, TRUST Fix All 220 Sealant, Guaranteed to work!

... what you need

425gm (#20067)

Fix All® 220 Sealant



100ml (#19391)
500ml (#19389)
1L (#19390)
5L (#19392)

Holdfast® 696 Surface Activator



#21100

Gorilla® PRO Gun



15mm x 1mm x 33m (#56663)

Gator® Bond Double Sided Tape

*NOTE: This information is intended as a guide only. If you are unsure please contact us for more detail. No responsibility will be accepted for incorrect installation. Test is best. Please refer to technical datasheet on our website. www.holdfast.co.nz

GUARANTEED NO RISK!

Brett Henderson
Managing Director, Holdfast NZ Ltd

