


NOVATHENE™

Low Density Polyethylene Pipe

Tried and true

Variable Pressure ratings



300 Series

Novathene™ has been a leading brand of low density polyethylene pipe in the New Zealand rural market for over 20 years. Its flexibility and thick wall section has consistently made it a reliable and economical choice for on farm day to day water reticulation needs.

PRODUCE CODE	MEAN BORE ID (mm)	PIPE SIZE OD (mm)	PRESSURE RATING*		STANDARD COIL SIZES (m)			
			(BAR)	(PSI)	25	50	100	200
300.15	12	17	9	131	✓	✓	✓	✓
300.20	19	25	8	116	✓	✓	✓	✓
300.25	25	31	6.5	94	✓	✓	✓	✓
300.32	31	38	5	72	✓	✓	✓	✓
300.40	38	44	4.5	65	✓	✓	✓	✓
300.50	50	57	3.5	51	✓	✓	✓	X

*Maximum operating pressure at 20°C

†Novathene™ is unsuitable for use with in-line bloat dispensing systems

Excellent Reasons to Specify NOVATHENE™:

- Economical** cost effective pipeline choice
- Flexible** easy uncoiling and laying
- Durable** thick wall section, strong
- Compatible** will connect to all New Zealand's leading brands of internal interference fit fittings
- Quality** manufactured and tested to NZS 7601