



Tile Fix

Cement-based dry-set mortar for wall and floor tiling.

PRODUCT

TILE FIX is a high quality water-resistant dry-set mortar for tile fixing. When used together with FIX ADMIX (in replacement of water), product performance is enhanced to meet higher requirement.

Ideal for installation of marble, granite, ceramic and homogenous tiles for walls and floors. Also suitable for application on gypsum board when used with FIX ADMIX.

TECHNICAL DATA AND PHYSICAL PROPERTIES

Colour	Grey/Off White
Binder	Cement
Filler	Graded limestone and/or sand
Additives	Water soluble additives to improve workability, open time, bond strength etc
Pot life	1 hour
Consumption	3-5 kg/m ² depending on substrate and back of tile
Water Demand	Approx. 32% or 8 litre per 25 kg bag

PROCEDURE

The substrate should be sound and free from materials affecting adhesion. Mix a 25 kg bag of TILE FIX into approx. 8 liters of FIX ADMIX or water. Allow mixture to stand for 10 minutes and mix again. Application with notched-trowel onto substrate or applying onto backface of tile are both recommendable. For big tiles and tiles with high ridges, combination of both methods gives best result. Substrates on which mortar had been spread should be tiled within 10 minutes. The tiles are firmly pressed onto the sub-base and immediately knocked into position. Tiling should not be done under direct sunshine or windy condition to avoid drying-out. To check the bond, at least 3/4 of the backside of a removed porous tile and the whole backside of a vitreous tile should be covered by the mortar.

PACKING AND STORAGE

TILE FIX is delivered in 25 kg bags. Storage life is 6 months if product is stored in a dry place.

Note: Because it is not possible to give specific instructions for the various site conditions or to control the applications, the information on this technical data sheet is for general guidance only.